

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 45 N., R. 53 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>I add the marks to read</p> <div style="text-align: center;"> <p>T45N R53E R54E 1/4 S13 S18 2020 1921</p> </div> <p>Set an aluminum sign post alongside iron post.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 45 N., R. 53 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of a Portion of the Survey Executed by U.S. Surveyor C.S. Swanholm in 1920 and 1921</p> <hr/> <p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°56'50" W., bet. secs. 13 and 24.</p>
2.494	<p>Point for the E-E-E-E 1/1024 sec. cor. of secs. 13 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>1/1024 2018</p> </div> <p>Set an aluminum sign post alongside stainless steel post.</p>
2.55	Barbed wire fence, bears N. 25° E. and S. 25° W.
8.95	Barbed wire fence, N. 60° E., 1.05 chs. dist. of fence corner with fences extending N. 60° E. and N. 45° W.
10.35	Barbed wire fence, N. 45° W., 0.70 chs. dist. of fence corner with fences extending N. 60° E. and N. 45° W.
11.15	Right bank of the Owyhee River, bears SE. and NW., thence across river, course NW.
11.95	Left bank of the Owyhee River, bears SE. and NW.
16.50	Barbed wire fence, bears N. and S.
16.952	Point for a witness point, at intersection of the easterly right-of-way line of Nevada State Route No. 225, with the line bet. secs. 13 and 24, hereinafter described.