SUBDIVISION OF SECTION 24, T. 45 N., R. 53 E., MOUNT DIABLO MERIDIAN

CHAINS	
	N. 0°01'50" E., on the computed N-S center line of the NE1/4NE1/4NE1/4 of sec. 24.
3.10	Barbed wire fence, bears S. 35° E. and N. 35° W.
4.988	The E-E-E 1/1024 sec. cor. of secs. 13 and 24.
	METES-AND-BOUNDS SURVEY OF A PORTION OF THE EASTERLY RIGHT-OF-WAY LINE OF NEVADA STATE ROUTE NO. 225, T. 45 N., R. 53 E., MOUNT DIABLO MERIDIAN, NEVADA
	From the point for a witness point, at intersection of the easterly right-of-way line of Nevada State Route No. 225 with the line bet. secs. 13 and 24.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	WP / S13
	S24
	2018
	From this point, a standard U.S. Dept. of Agriculture Bureau of Public Roads highway station, utilized to determine the centerline of the right-of-way, monumented with an iron post, 2 1/2 ins. diam., projecting 12 ins. above ground, with brass cap mkd. ELEVATION 4093+90.78 5745.09 FEET 1939, bears S. 45°30′20″ E., 28.565 chs. dist.
	From this same point, a standard U.S. Dept. of Agriculture Bureau of Public Roads highway station utilized to determine the centerline of the right-of-way, monumented with an iron post, 2 1/2 ins. diam., projecting 6 ins. above ground, with brass cap mkd. ELEVATION 4093+90.78 FEET 1939, bears S. 43°24'40" E., 29.450 chs. dist.
	Set an aluminum sign post alongside stainless steel post.
	Thence along the arc of a circular curve to the right having a radius of 1550.00 ft., the long chord of said arc bears N. 10°40′50″ W., 1.676 chs. dist., on the easterly right-of-way line of Nevada State Route No. 225.
1.40	Dirt road, 35 lks. wide, bears N. 85° E. and S. 85° W.
1.676	Point of Tangency and point for a witness point, falls near the base of a power pole with electric lines extending into the ground.
į	Set a magnetic nail, 6 ins. long, mkd. MAG, flush with the ground