DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 19 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

| CHAINS 40.566 | The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., hereinbefore described. |
|------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 18, T. 19 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA |
| | Reestablishment of a Portion of the Survey Executed by Cadastral Surveyor R.A. Zaninovich in 1999-2000 |
| | From the 1/4 sec. cor. of secs. 17 and 18, hereinbefore described. |
| | S. 89°44'20" W., on the E-W center line of sec. 18. |
| 0.40 | Graded dirt road, 30 lks. wide, bears N. and S. |
| 6.061 | The witness point at the intersection of a line parallel to and 400 feet westerly of the line bet. secs 17 and 18, with the E-W center line of sec. 18, hereinafter described. |
| 21.378 | The C-E 1/16 sec. cor. of sec. 18, monumented with a rebar, 5/8 in. diam., 36 ins. long, firmly set, flush with the surface of the ground, with aluminum cap mkd. as described in the field notes of the subdivision of section 18, T. 19 S., R. 62 E., executed under Group No. 780. |
| | from which the reference monuments established by Bartlett C. Dalton, Nevada Professional Land Surveyor No. 10160, in 1999, as recorded in Clark County, Nevada, File No. 102, Page 51 of Surveys |
| | A rebar, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with aluminum cap mkd. CNLV SURVEY MONUMENT RM 71.31 PLS 10160, bears N. 45°20' E., 108.0 lks. dist. |
| | A rebar, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with aluminum cap mkd. CNLV SURVEY MONUMENT RM 75.11 PLS 10160, bears S. 45°27' E., 113.8 lks. dist. |
| | A rebar, 5/8 in. diam., firmly set, projecting 1 in. above the ground, with aluminum cap mkd. CNLV SURVEY MONUMENT RM 68.14 PLS 10160, bears S. 45°20' W., 103.2 lks. dist. |
| | A rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, with aluminum cap mkd. CNLV SURVEY MONUMENT RM 63.38 PLS 10160, bears N. 45°27' W., 96.0 lks. dist. |
| | At the corner point |
| | |
| | |