

DEPENDENT RESURVEY OF THE SIXTH STANDARD PARALLEL SOUTH,  
THROUGH RANGE 58 EAST, MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 94.808</p>	<p>Point for the standard cor. of Tps. 24 S., Rs. 57 and 58 E., at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 7 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>SC T24S R57E   R58E S36   S31</p> <hr style="width: 50%; margin: auto;"/> <p>2010</p> </div>
	<p>DEPENDENT RESURVEY OF THE SIXTH STANDARD PARALLEL SOUTH, THROUGH A PORTION OF RANGE 57 EAST, MOUNT DIABLO MERIDIAN, NEVADA</p>
	<p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyors J.M. Brunt and W.H. Proctor in 1881</p>
	<p>From the standard cor. of Tps. 24 S., Rs. 57 and 58 E., hereinbefore described.</p> <p>N. 89°38'50" W., on the S. bdy. of sec. 36.</p>
<p>5.060</p>	<p>The closing cor. of Tp. 25 S., Rs. 57 and 58 E., monumented with a brass tablet, 3 1/4 ins. diam., firmly set in solid rock, with top mkd. as described in the field notes of the dependent resurvey of T. 25 S., R. 58 E., executed concurrently under Group No. 891.</p>
<p>47.404</p>	<p>The standard 1/4 sec. cor. of sec. 36, T. 24 S., R. 57 E., monumented with a limestone, 17x12x7 ins., firmly set in a mound of stone, 4 ft. diam., 2 ft. high, mkd. 1/4 on the N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 5 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>SC T24S R57E 1/4 S36</p> <hr style="width: 50%; margin: auto;"/> <p>2010</p> </div> <p>Deposit the mkd. stone alongside the stainless steel post.</p>