

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Reestablishment of the Survey Executed by U.S. Deputy Surveyor T.A. Magee in 1883</p> <hr/>
	<p>From the cor. of secs. 35 and 36, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 1°15'10" E., bet. secs. 35 and 36.</p>
3.70	Top of ridge, bears NE. and SW.
13.80	Wash, 30 lks. wide, drains NE.
39.70	Wash, 20 lks. wide, drains NE.
40.308	<p>Point for the 1/4 sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T25S R58E 1/4 S35 S36</p> <p style="text-align: center;">2011</p>
54.90	Dirt road, 12 lks. wide, bears ESE. and WNW.
75.40	Wash, 2 chs. wide, drains ESE.
80.616	<p>Point for the cor. of secs. 25, 26, 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T25S R58E S26 S25 S35 S36</p> <p style="text-align: center;">2011</p>
	<hr/> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°50'10" W., bet. secs. 25 and 36.</p>
17.10	Dirt road, 15 lks. wide, bears N. and S.
40.215	<p>The 1/4 sec. cor. of secs. 25 and 36, monumented with a limestone, 21x17x9 ins., firmly set in a mound of stone, 2 1/2 ft. diam., 1 ft. high, mkd. 1/4 on the S. face.</p> <p>At the corner point</p>