

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 1854,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

Reestablishment of the Survey Executed by  
U.S. Deputy Mineral Surveyor H.W. Newby in 1899

Full Moon lode

From Cor. No. 1, Mineral Survey No. 1854, Full Moon lode, perpetuated by James J. Owens, Nevada Professional Land Surveyor No. 2884, in 1998, monumented with a rebar, 5/8 in. diam., 12 ins. long, firmly set in a mound of stone, 2 1/2 ft. diam., 1 ft. high, with aluminum cap mkd. MS1854 1-FULL MOON OWENS PLS 2884, with a wood post, 3x3 ins., 3 ft. long, lying loose alongside, no marks visible, as recorded in Clark County, Nevada, File 94, Page 40 of Surveys. This is accepted as a careful and faithful perpetuation of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.

T25S R58E  
S16



2011

Deposit the rebar and invert and reset the wood post alongside the stainless steel post.

Thence S. 16°21'20" E., on line 1-2, Mineral Survey No. 1854, Full Moon lode.

9.644

Cor. No. 2, Mineral Survey No. 1854, Full Moon lode, perpetuated by James J. Owens, Nevada Professional Land Surveyor No. 2884, in 1998, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set in a mound of stone, 2 ft. diam., 1 ft. high, with aluminum cap mkd. MS1854 2-FULL MOON OWENS PLS 2884, with a wood post, 3x3 ins., 4 ft. long, lying loose alongside, mkd. 1854-2, as recorded in Clark County, Nevada, File 94, Page 40 of Surveys.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.