

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 24 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>T24S R59E S30 1/4 — S31 2015</p> <p>Insert the rebar within the stainless steel post and bury the mkd. stone within the mound of stone alongside the stainless steel post.</p> <hr/> <p>N. 88°52'20" W., beginning new measurement.</p> <p>10.55 Power line, bears S. 55° E. and N. 55° W.</p> <p>10.75 Dirt road, 12 lks. wide, bears S. 55° E. and N. 55° W.</p> <p>32.20 Trail road, 10 lks. wide, bear N. 75° E. and S. 75° W.</p> <p>39.962 The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. as described in the field notes of the 2012-14 dependent resurvey of a portion of the E. bdy., T. 24 S., R. 58 E., executed under Contract No. L06PC05105, Group No. 887, with a steel fence post set alongside.</p> <p>Corner located beneath power line, bears N. and S.</p> <hr/> <p>SUBDIVISION OF SECTION 31, T. 24 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the standard 1/4 sec. cor. of sec. 31, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, and in a collar of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of the Sixth Standard Parallel South, through a portion of R. 59 E., executed concurrently under this same Group.</p> <p>N. 0°01'40" W., on the N-S center line of sec. 31.</p> <p>40.579 Point for the center 1/4 sec. cor. of sec. 31, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p>T24S R59E C 1/4 S31 2015</p> <p>50.95 Nevada State Route No. 161, asphalt surface, 30 lks. wide, bears S. 60° E. and N. 60° W.</p>
--------	---