

DEPENDENT RESURVEY OF THE SIXTH STANDARD PARALLEL SOUTH,
THROUGH A PORTION OF RANGE 59 EAST,
MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this same point, a rebar, 5/8 in. diam., loosely set by person(s) unknown, projecting 3 ins. above the ground, bears N. 69°01' W., 0.073 chs. dist. This rebar was not utilized during the course of this survey.</p> <hr/> <p>DEPENDENT RESURVEY OF THE SIXTH STANDARD PARALLEL SOUTH, THROUGH A PORTION OF RANGE 58 EAST, MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyors J.W. Brunt and W.H. Proctor in 1881, and a Portion of the Dependent Resurvey Executed by Professional Land Surveyor B.D. Hatter, Cadastral Surveyor B.R. Clifford and Surveying Technician M.G. Petrosine in 2010-21</p> <hr/> <p>From the standard cor. of Tps. 24 S., Rs. 58 and 59 E., hereinbefore described.</p> <p>N. 89°50'00" W., on the S. bdy. of sec. 36.</p> <p>5.20 Wash, drains SE.</p> <p>6.350 The closing cor. of Tps. 25 S., Rs. 58 and 59 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, and in a collar of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of the E. bdy., T. 25 S., R. 58 E., executed under Contract No. L06PC05105, Group No. 891.</p> <p>40.462 The standard 1/4 sec. cor. of sec. 36, T. 24 S., R. 58 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, flush in a mound of stone, 4 ft. diam., 1/2 ft. high, with brass cap mkd. as described in the field notes of the 2010-21 dependent resurvey of the Sixth Standard Parallel South, through R. 58 E., executed under Contract No. L06PC05105, Group No. 887.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 25 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor T.A. Magee in 1883</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8, perpetuated by Byron E. Johnson, Professional Land Surveyor No. 9390, in 2002, monumented with a rebar, 5/8 in. diam., 12 ins. long, firmly set, flush with the surface of the ground, with aluminum cap mkd. B JOHNSON PLS9390, and a volcanic stone, 13x8x6 ins. (Record: limestone, 16x9x8 ins.), mkd. with 5 notches on two edges, lying loose alongside, within a mound of stone, 4 ft. diam., 1 1/2 ft. high, as recorded in Clark County, Nevada, File No. 122, Page 87 of Surveys.</p> <p>At the corner point</p>
--------	---