DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 25 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

<div align="center">

T24S R59E
S31
———
S 6 | S 5
T25S R59E
CC

2015

</div>

From this point, the standard cor. of secs. 31 and 32, T. 24 S.,
R. 59 E., hereinbefore described, bears S. 89°53'10" E.,
8.545 chs. dist.

The point for the 1/4 sec. cor. of sec. 6 only, T. 25 S.,
R. 59 E., is on the Sixth Standard Parallel South and at
proportional distance on the N. bdy. of sec. 6.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
26 ins. in the ground, over a plastic-encased magnet, with brass
cap mkd.

<div align="center">

T24S   R59E
———
1/4 S 6
T25S R59E

2015

</div>

From this point, the standard 1/4 sec. cor. of sec. 31,
T. 24 S., R. 59 E., hereinbefore described, bears
N. 89°43'50" E., 9.004 chs. dist.

<div align="center">

SUBDIVISION OF SECTION 6,
T. 25 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

</div>

From the 1/4 sec. cor. of secs. 6 and 7.

N. 1°24'20" W., on the N-S center line of sec. 6.

20.046   Point for the center S 1/16 sec. cor. of sec. 6.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, over a plastic-encased magnet, with brass
cap mkd.

<div align="center">

C
S 1/16 | S 6
C

2015

</div>