

DEPENDENT RESURVEY OF A PORTION OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 34,
T. 21 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

| CHAINS | |
|--------|---|
| | <p>Reestablishment of a Portion of the Survey Executed by Cadastral Surveyor, R.E. Williams, in 1991-1996</p> |
| | <p>From the center 1/4 sec. cor. of sec. 34, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the 1991 - 1996 subdivision of section 34, T. 21 S., R. 63 E., executed under Group No. 713, with a mound of stone, 2 1/2 ft. diam., 1 1/2 ft. high, W. of the cor.</p> |
| | <p>S. 89°33'00" W., on a portion of the E-W center line of sec. 34.</p> |
| 12.00 | Enter disturbed ground. |
| 14.25 | SNWA water line, bears N. and S. |
| 16.153 | <p>The point for a witness point at the intersection of the easterly line of Bureau of Land Management right-of-way reservation N-73903 with the E-W center line of sec. 34, hereinafter described.</p> |
| 16.60 | Leave disturbed ground. |
| 17.90 | Asphalt recreation path, bears NE. and WSW. |
| 20.162 | <p>The C-W 1/16 sec. cor. of sec. 34, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, in a collar of stone, with brass cap mkd. as described in the field notes of the 1991 - 1996 subdivision of section 34, T. 21 S., R. 63 E., executed under Group No. 713.</p> |
| | <p>From this corner, a bent brass rod with no cap (1991 Record, U.S.G.S. Benchmark "HLS 1970", aluminum rod), bears N. 44°00' E., 2.88 chs. dist.</p> |
| | <p>From this same corner, a Nevada Department of Transportation right-of-way station 182+21.54, monumented with a concrete block, 6 ins. square, firmly set, projecting 5 ins. above the ground, with a nail in the center, and a N. on NNW. side, bears S. 47°37'40" W., 7.494 chs. dist.</p> |
| | <p>From the C-S 1/16 sec. cor. of sec. 34, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the 1991 - 1996 subdivision of section 34, T. 21 S., R. 63 E., executed under Group No. 713, with a mound of stone, 2 ft. diam., 1 ft. high, W. of the cor.</p> |
| | <p>S. 89°49'00" W., on a portion of the E-W center line of the SW1/4 of sec. 34.</p> |
| 9.10 | Enter disturbed ground. |
| 12.05 | Bladed road, 20 lks. wide, bears SE. and NW. |
| 16.20 | Leave disturbed ground. |