

DEPENDENT RESURVEY OF PORTIONS OF A METES-AND-BOUNDS SURVEY OF  
A PORTION OF THE NORTHERLY RIGHT-OF-WAY OF  
LAKE MEAD PARKWAY (DRIVE),  
T. 21 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">Reestablishment of Portions of the Survey Executed by Cadastral Surveyor, R.E. Williams, in 1991-1996</p> <hr/>
	<p>From the witness point at the intersection of the N-S center line of sec. 34 with the northerly right-of-way of Lake Mead Parkway (Drive), monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, in a collar of stone, with brass cap mkd. as described in the field notes of the 1991 - 1996 subdivision of section 34, T. 21 S., R. 63 E., executed under Group No. 713.</p>
	<p>S. 59°22'30" W., along a portion of the northerly right-of-way of Lake Mead Parkway (Drive).</p>
17.525	<p>The point for a witness point at the intersection of the easterly line of Bureau of Land Management right-of-way reservation N-73903 with the northerly right-of-way of Lake Mead Parkway (Drive), hereinafter described.</p>
22.480	<p>The point for a witness point at the intersection of the N-S center line of the NW1/4 of sec. 34 with the northerly right-of-way of Lake Mead Parkway (Drive), hereinbefore described.</p>
32.086	<p>Beginning of curve, point not monumented.</p> <hr/>
	<p>Along the arc of a circular curve to the right, having a radius of 3,800 ft.; the chord of said arc bears S. 59°36'30" W., 0.469 chs. dist.</p>
0.469	<p>The witness point at the intersection of the E-W center line of sec. 34 with the northerly right-of-way of Lake Mead Parkway (Drive), monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, 18 ins. below the surface of the ground, with brass cap mkd. as described in the field notes of the 1991 - 1996 subdivision of section 34, T. 21 S., R. 63 E., executed under Group No. 713, with an iron pipe, 2 1/2 ins. diam., bent over alongside.</p> <p>Cor. is located below overhead power line, bears N. and S.</p> <hr/>
	<p>From the witness point at the intersection of the N-S center line of the NW1/4SW1/4 of sec. 34 with the northerly right-of-way of Lake Mead Parkway (Drive), monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, 12 ins. below the surface of the ground, with brass cap mkd. as described in the field notes of the subdivision of section 34, T. 21 S., R. 63 E., executed under Group No. 713, with a rebar, 5/8 in. diam., 16 ins. long, buried alongside and with a steel pipe, 2 1/2 ins. diam., projecting 30 ins. above the ground, firmly set alongside.</p> <p>Cor. is located below overhead power line, bears N. and S.</p>
	<p>Continuing along circular curve to the right, having a radius of 3,800 ft., the chord of said arc bears S. 66°19'20" W., 10.687 chs. dist.</p>