

## TOWNSHIP 23 NORTH, RANGE 23 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>The NAD 1983 (2011) (EPOCH:2010.0000) geographic position, of the following corners were determined from GNSS static observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) DE6260 STEA STEAD COOP CORS ARP, DN5642 P149 BABBITPK_CN2008 CORS ARP and AI8814 UPSA UPSA_BRGN_NV1997 CORS ARP, and carried forward by RTK observations.</p> <p>The 1/4 sec. cor. of secs. 19 and 24, on the E. bdy. of the Tp., is as follows:</p> <p>Latitude: 39°50'51.622" N. Longitude: 119°20'25.822" W.</p> <p>The 1/4 sec. cor. of sec. 35 only, T. 24 N., R. 23 E., is as follows:</p> <p>Latitude: 39°53'59.620" N. Longitude: 119°21'57.978" W.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY, T. 24 N., R. 23 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor S.W. Foreman in 1865, the Resurvey Executed by U.S. Deputy Surveyor R. Gorlinski in 1909, a Portion of the Resurvey Executed by U.S. Surveyor G.P. Harrington in 1911, and the Resurvey Executed by U.S. Surveyor W.A. Pray in 1916</p> <hr/> <p>Beginning at the cor. of Tps. 24 N., Rs. 23 and 24 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 12 ins. above the ground, in a scattered mound of stone, with brass cap mkd. as described in the field notes of the 1916 dependent resurvey of the fractional S. bdy., T. 24 N., R. 23 E., executed under Group Nos. 33 and 47.</p> <p>Rebuild the mound of stone, 3 ft. base, to top of brass cap.</p> <p>N. 89°56'40" W., on the S. bdy. of sec. 36.</p> <p>Gentle slope to the W., scattered brush.</p>
10.973	<p>The closing cor. of Tps. 23 N., Rs. 23 and 24 E., hereinafter described.</p>
39.963	<p>The 1/4 sec. cor. of sec. 36 only, monumented with the remains of iron post fragments, size undetermined, with a volcanic stone, 14x8x8 ins. (1916 Record, 10x8x6 ins.), firmly set alongside, projecting 6 ins. above the ground, mkd. 1/4 on the N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p>