

SUBDIVISION OF SECTION 36,
T. 24 N., R. 23 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From the 1/4 sec. cor. of sec. 36 only, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, flush in a collar of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the S. bdy. of T. 24 N., R. 23 E., executed concurrently under this same group.</p> <p>N. 0°07'30" E., on the N-S center line of sec. 36.</p> <p>Over near level land with scattered brush.</p>
19.985	<p>Point for the C-S 1/16 sec. cor. of sec. 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>C</p> <p>S 1/16 S36</p> <p>C</p> <p>2019</p> </div> <p>Over near level land with scattered brush.</p>
20.80	<p>Dirt road, 15 lks. wide, bears N. 33° E. and S. 23° W.</p>
39.970	<p>Point for the center 1/4 sec. cor. of sec. 36, at intersection with E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T24N R23E</p> <p>C 1/4 S36</p> <p>2019</p> </div>
59.946	<p>Point for the C-N 1/16 sec. cor. of sec. 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>C</p> <p>N 1/16 S36</p> <p>C</p> <p>2019</p> </div>