

DEPENDENT RESURVEY OF A PORTION OF
THE PYRAMID LAKE INDIAN RESERVATION BOUNDARY,
T. 21 N., R. 24 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS
40.261

The true point for Mile Post 12 on the E. bdy. of the Pyramid Lake Indian Reservation, monumented with a brown volcanic stone, 12x12 ins. (1911 Record, 24x18x12 ins.), firmly set, projecting 16 ins. above the ground, mkd. 12 M on S. face and PL on E. face. W. of and alongside is the witness cor. to Mile Post 12, monumented with an iron post, 1 in. diam., firmly set, projecting 20 ins. above the ground, with brass cap mkd. as described in the field notes of the 1911 retracement of the E. bdy. of the Pyramid Lake Indian Reservation in T. 22 N., R. 24 E., executed under instructions dated April 27, 1911.

Remark brass cap of witness cor. to read:

WC
T22N R24E
S34
PLIR \ →
12 M

2022
1911

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 22 N., R. 24 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of a Portion of the Survey Executed by
U.S. Deputy Surveyor S.W. Foreman in 1865,
a Portion of the Resurvey Executed by
U.S. Deputy Surveyor J.B. Menardi in 1905,
a Portion of the Retracement Executed by
G.P. Harrington in 1911, and
a Portion of the Retracement Executed by
U.S. Surveyor A.T. Harris in 1915

From the cor. of secs. 35 and 36 only, T. 22 N., R. 24 E., monumented with a basalt stone, 16x8x6 ins. (1915 Record, lava stone, 10x10x12 ins.), firmly set, projecting 9 ins. above the ground, mkd. with 1 notch on E. edge and 5 notches on W. edge, with a mound of stone, 3 ft. diam., 1/2 ft. high, N. of cor.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

T22N R24E
S35 | S36
—
T21N R24E
S 1

2020