

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 22 N., R. 24 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

From this cor., a mound of stone, 3 ft. diam., 2 ft. high, bears
N. 7° W., 10 lks. dist.

Witness cor. is located on rocky SE. facing slope.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 24 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of a Portion of the Survey Executed by
U.S. Deputy Surveyor J.B. Menardi in 1905
and a Portion of the Resurvey Executed by U.S. Surveyor
G.P. Harrington in 1911

From the cor. of secs. 25, 26, 35 and 36, monumented with a
granite stone, 17x10x10 ins. (1905 Record, basalt stone,
14x10x10 ins.), firmly set, projecting 11 ins. above the ground,
mkd. with 1 notch on the E. edge and 1 notch on the S. edge.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, over a plastic-encased magnet, with brass
cap mkd.

T21N R24E	
S26	S25
—	
S35	S36

2020

Bury the mkd. stone inverted alongside the stainless steel post.
S. 89°55'00" W., bet. secs. 26 and 35.

6.00

Sand hill.

40.016

The 1/4 sec. cor. of secs. 26 and 35, monumented with a basalt
stone (1911 Record, granite stone), 14x8x8 ins., firmly set,
projecting 8 ins. above the ground, mkd. 1/4 on the N. face.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
22 ins. in the ground, over a plastic-encased magnet, with brass
cap mkd.

T21N R24E	
S26	
1/4	—
S35	

2020