

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY
T. 20 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

Reestablishment of a portion of the Survey executed by
U.S. Deputy Surveyor R.H. Woods in 1881

Beginning at the cor. of secs. 2, 3, 34, and 35, determined by person(s) unknown, monumented with a MAG nail, firmly set, flush with the surface of the asphalt, no mks. visible. This position has been adopted by numerous professional land surveyors and correlates well with the position perpetuated by the Department of the Army-CORPS of Engineers, in 1948, as recorded in Clark County, Nevada, File 1, Page 11 of Surveys, and is accepted as the best available evidence of the position of the original corner

from which accessories established by Barry D. Bruland, Nevada Professional Land Surveyor No. 8352, no record found

An aluminum cap, 2 ins. diam., firmly set in top of concrete curb, mkd. RM 90.98 PLS 8352, bears N. 29°31'10" E., 137.7 lks. dist.

An aluminum cap, 2 ins. diam., firmly set in top of concrete curb, mkd. RM 75.27 PLS 8352, bears N. 36°40'40" E., 114.2 lks. dist.

An aluminum cap, 2 ins. diam., firmly set in top of concrete curb, mkd. RM 93.30 PLS 8352, bears N. 68°17'20" E., 141.3 lks. dist.

An aluminum cap, 2 ins. diam., firmly set in top of concrete curb, mkd. RM 101.72 PLS 8352, bears N. 70°06'50" E., 154.1 lks. dist.

and the accessories established by Kevin E. Mott, Nevada Professional Land Surveyor No. 8662, no record found

An aluminum cap, 1 1/2 ins. diam., firmly set in top of concrete curb, mkd. RM PLS 8662, bears S. 61°18'50" W., 173.2 lks. dist.

An aluminum cap, 1 1/2 ins. diam., firmly set in top of concrete curb, mkd. ORION RM PLS 8662, bears S. 63°41'30" W., 187.6 lks. dist.

and an accessory established by person(s) unknown

An aluminum cap, 2 ins. diam., firmly set in top of concrete curb, mkd. 83.12, bears N. 65°20'40" E., 125.8 lks. dist.

From this cor., a position determined by person(s) unknown, monumented with a MAG nail, with underlying plastic washer 1/2 in. diam., mkd. SURVEY MARKER DO NOT REMOVE, and an aluminum shiner, 2 ins. diam., firmly set, flush with the surface of the asphalt, in center of painted photo panel, bears N. 65°04'20" E., 0.050 chs. dist. The position of this monument does not correlate well with the position adopted by numerous professional land surveyors and is not utilized during the course of this survey.