

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T16N R63E S12 1/4 ——— S13 2015
	Bury iron pipe alongside stainless steel post.
	Cor. is located on W. side of a barbed wire fence, 4 strands, bears N. and S.
	—————
	S. 89°59'20" W., beginning new measurement.
4.50	Old railroad grade, bears NE. and SW.
7.20	Barbed wire fence corner, extends N., S. and W.
12.75	Wash, 65 lks. wide, 2 ft. deep, bears NNW. and SE.
19.55	Downed barbed wire fence corner, with fences extending E., S. and W.
19.916	The W 1/16 sec. cor. of secs. 12 and 13, determined by person(s) unknown, monumented with a rebar, 1/2 in. diam., firmly set, projecting 2 ins. above the ground, no record found. This is accepted as a careful and faithful determination of the position of the corner.
	Cor. is located under a barbed wire fence, bears E. and W.
	—————
	S. 89°59'20" W., beginning new measurement.
1.00	Wash, 12 lks. wide, 2 ft. deep, bears N. and S.
19.916	The cor. of secs. 11, 12, 13 and 14.
	—————
	SUBDIVISION OF SECTION 13, T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA
	From the 1/4 sec. cor. of secs. 13 and 24.
	N. 0°02'00" E., on the N-S center line of sec. 13.
	Over valley floor, covered with sagebrush, rabbitbrush and grasses.
20.325	Point for the C-S 1/16 sec. cor. of sec. 13.
	POINT NOT MONUMENTED
26.50	Power line, bears N. 37 1/4° E. and S. 37 1/4° W.