DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY.

## T. 16 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA CHAINS Reestablishment of a Portion of the Dependent Resurvey Executed by J.D. Sorensen, Cadastral Surveyor, in 1967 From the cor. of secs. 6 and 7 only, T. 16 N., R. 28 E., monumented with an iron post, 2 1/2 ins. diam., firmly set, flush with the surface of the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the fractional W. bdy., T. 16 N., R. 28 E., executed under Group No. 447, with a mound of stone, 3 ft. diam., 1 ft. high, E. of cor. N. 0°18'40" W., on the W. bdy. of sec. 6. 19.70 Center of dirt road known as Simpson Road, bears NE. and SW. The E. 1/4 sec. cor. of sec. 1, T. 16 N., R. 27 E., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 38.789 4 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of the subdivisional lines, T. 16 N., R. 27 E., executed under Group No. 447, with a mound of stone, 2 ft. diam., 1 1/2 ft. high, W. of cor. 40.248 The W 1/4 sec. cor. of sec. 6, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the fractional W. bdy., T. 16 N., R. 28 E., executed under Group No. 447, with a mound of stone, 3 ft. diam., 1 ft. high, E. of cor. DEPENDENT RESURVEY OF PORTIONS OF THE SOUTH BOUNDARY, T. 17 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA Reestablishment of Portions of the Independent Resurvey Executed by J.D. Sorensen, Cadastral Surveyor, in 1967 From the cor. of Tps. 16 and 17 N., Rs. 27 and 28 E., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the fractional W. bdy., T. 16 N., R. 28 E., executed under Group No. 447, with a mound of stone, 3 ft. diam., 1 ft. high, S. of cor. WEST, on the S. bdy. of sec. 36. 22.510 The N. 1/4 sec. cor. of sec. 1, T. 16 N., R. 27 E., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 1 in. above the ground, with brass cap mkd. as described in the field notes of the survey of the subdivisional lines, T. 16 N., R. 27 E., executed under Group No. 447, with a mound of stone, 2 ft. diam., 1 ft. high, S. of cor. Cor. is located 15 lks. S. of a barbed wire fence, bears E. and W.