

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 16 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Reestablishment of a Portion of the Survey Executed by G.W. Ridgway, U.S. Cadastral Engineer, in 1923</p> <hr/>
	<p>From the cor. of secs. 1, 2, 11 and 12, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above a mound of stone, 3 ft. diam., 1 1/2 ft. high, with brass cap mkd. as described in the field notes of the survey of the subdivisional lines of T. 16 N., R. 26 E., executed under Group No. 101.</p>
	<p>N. 0°10'50" W., bet. secs. 1 and 2.</p>
20.20	<p>Spur, slopes W.</p>
40.088	<p>Point for the 1/4 sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to solid rock, over a plastic encased magnet, and in a mound of stone, 4 1/2 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T16N R26E 1/4 S 2 S 1 2023</p>
	<p>from which</p>
	<p>The marks XBO on a basalt boulder 4 1/2 x 3 1/2 x 2 1/2 ft., bears S. 31°42' E., 68.2 lks. dist. Marks on the SE. edge of the top face.</p>
	<p>The marks XBO on a basalt boulder 4 1/2 x 2 1/2 x 1 1/2 ft., bears S. 42°32' W., 110.1 lks. dist. Marks on the W. edge of the top face.</p>
	<p>From this point, United States Geological Survey benchmark station "111 GWM" bears N. 17°47'50" E., 2.591 chs. dist., monumented with a brass tablet, 4 ins. diam., firmly set in a concrete cylinder, 8 ins. diam., projecting 10 ins. above the ground, with top mkd.</p>
	<p style="text-align: center;">US Geological Survey Elevation Above Δ Sea 4313 111 GWM 1950</p>
41.00	<p>Center of dirt road known as Simpson Road, 20 lks. wide, bears NE. and SW.</p>
58.50	<p>Enter wash, bank bears ENE. and WSW.</p>
60.132	<p>Point for the N 1/16 sec. cor. of secs. 1 and 2.</p>