## DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 16 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	Cor. located under a barbed wire fence, bears E. and W.
	SUBDIVISION OF SECTION 6, T. 16 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA
	From the 1/4 sec. cor. of secs. 6 and 7.
	N. $0^{\circ}25'00"$ W., on the N-S center line of sec. 6.
37.80	Dirt road known as Simpson Road, 17 lks. wide, bears N. 63° E. and S. 63° W.
40.366	Point for the center 1/4 sec. cor. of sec. 6, at intersection with the E-W center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T16N R28E C 1/4 S6
	2024
	From this point, a wood post, of unknown origin, 4x4 ins., firmly set, projecting 5 ins. above the ground, no mks., bears S. 13°27′50″ E., 3.461 chs. dist.
80.515	The 1/4 sec. cor. of secs. 6 and 31, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, in a collar of stone, with brass cap mkd. as described in the field notes of the 1990-91 dependent resurvey of a portion of the S. bdy., T. 17 N., R. 28 E., executed under Group No. 694.
	Cor. is located 1 lk. N. of a barbed wire fence, bears E. and W.
	From the 1/4 sec. cor. of secs. 5 and 6.
	N. 89°51'50" W., on the E-W center line of sec. 6.
33.80	Dirt road known as Simpson Road, 17 lks. wide, bears N. 75° E. and S. 75° W.
39.790	The center 1/4 sec. cor. of sec. 6.
79.441	The 1/4 sec. cor. of sec. 6, only, on the W. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set projecting 5 ins. above the ground, with brass cap mkd. as described in the field notes of the 1967 dependent resurvey of the fractional W. bdy., T. 16 N., R. 28 E., executed under Group No. 447, with a mound of stone, 3 ft. diam., 1 ft. high, E. of cor.