

RETRACEMENT OF THE NEVADA-UTAH STATE LINE
 BETWEEN THE WITNESS CORNER FOR MILE POST NO. 41
 AND MILE POST NO. 44

<p>CHAINS 79.943</p>	<p>Mile Post No. 44 on the Nevada-Utah State Line, monumented with an iron post, 2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. as described in the field notes of the 1936-1937 Dependent Resurvey of the Nevada-Utah State Line, executed under Group No. 194, with an embedded mound of stone, 3 ft. diam., W. of the cor.</p>
<hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 33 N., R. 70 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>	
<p>Reestablishment of a Portion of the Survey Executed by Cadastral Engineer G.M. Litz in 1947</p> <hr/>	
	<p>From the cor. of secs. 27, 28, 33, and 34, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the 1947 survey of the subdivisional lines, T. 33 N., R. 70 E., executed under Group No. 334, with a mound of stone, 3 ft. diam., 1 1/2 ft. high, W. of the cor.</p> <p>EAST, bet. secs. 27 and 34.</p>
12.352	<p>The witness point at the intersection with the metes-and-bounds survey in secs. 15, 22, and 27, hereinafter described.</p>
40.014	<p>The 1/4 sec. cor. of secs. 27 and 34, monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. as described in the field notes of the 1947 survey of the subdivisional lines, T. 33 N., R. 70 E., executed under Group No. 334, with a mound of stone, 2 1/2 ft. diam., 1 ft. high, N. of the cor.</p>
<hr/> <p>From the cor. of secs. 21, 22, 27, and 28, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the 1947 survey of the subdivisional lines, T. 33 N., R. 70 E., executed under Group No. 334, with a scattered mound of stone, 3 ft. diam., 1/2 ft. high, W. of the cor.</p>	
<p>S. 89°59'50" E., bet. secs. 22 and 27.</p>	
12.350	<p>The witness point at the intersection with the metes-and-bounds survey in secs. 15, 22, and 27, hereinafter described.</p>
24.6	<p>Improved road, 40 lks. wide, bears N. and S.</p>
40.016	<p>The 1/4 sec. cor. of secs. 22 and 27, monumented with the rusted remains of an iron post, 1 in. diam., firmly set, projecting 1 in. above the ground, with the top portion of the iron post, 6 ins. long, with brass cap mkd. as described in the field notes of the 1947 survey of the subdivisional lines, T. 33 N., R. 70 E., executed under Group No. 334, lying loose alongside, with a mound of stone, 2 ft. diam., 1/2 ft. high, N. of the cor.</p> <p>At the corner point</p>