

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4699,  
SALT SPRING NUMBER TWO LODGE,  
T. 33 N., R. 70 E., MOUNT DIABLO MERIDIAN, NEVADA AND  
T. 1 S., R. 19 W., SALT LAKE MERIDIAN, UTAH

CHAINS	
	<p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by U.S. Mineral Surveyor C.F. De Armond in 1927</p> <hr style="width: 20%; margin: auto;"/> <p>From Cor. No. 2, Mineral Survey No. 4699, Salt Spring Number Two lode, determined at the position of the disintegrating, rusted remains of a rebar, recovered 3 ins. below the surface of the ground. This position is in substantial agreement with the official record, has long-standing local acceptance, and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 2 ins. below the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center; border: 1px solid black; padding: 5px; width: fit-content; margin: 10px auto;">       MS4699        SS2        2     </div> <p style="text-align: center;">2024</p> <p>Bury the remains of the rebar alongside the stainless steel post.</p> <p>N. 89°51'50" W., on line 2-3, Mineral Survey No. 4699, Salt Spring Number Two lode.</p> <p>0.087 Point of intersection with the Nevada-Utah State Line.</p> <p>POINT NOT MONUMENTED</p> <p>From this point, the witness cor. to Mile Post No. 41 on the Nevada-Utah State Line, hereinbefore described, bears N. 0°18'20" E., 29.14 chs. dist.</p> <p>From the same point, Mile Post No. 42 on the Nevada-Utah State Line, hereinbefore described, bears S. 0°18'20" W., 38.294 chs. dist.</p> <p>7.504 Angle Point No. 3 of the metes-and-bounds survey of a portion of Parcel B in secs. 15 and 22, hereinafter described.</p> <p>9.093 Cor. No. 3, Mineral Survey No. 4699, Salt Spring Number Two lode, monumented with the rusted remains of a rebar, 5/8 in. diam., firmly set, 1 in. below the surface of the ground. This position is in substantial agreement with the official record, has long-standing local acceptance, and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. below the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p>