

-1-

Survey commenced June 10, 1912, and executed with W. & L. E. Gurley light mountain transit #553, the horizontal limb of which has two double opposite verniers reading to single minutes of arc.

I examine the adjustments of the transit and find them correct.

Beginning at the north monument of the meridian established at Fallon, Nevada, by Polaris observation and reported in field notes of the survey of Section 12, T. 18 N., R. 29 E., M. D. M., I sight on a flag placed northwesterly, finding it to bear N.44°37' W. From said flag the $\frac{1}{4}$ corner, Section 25 and 26, T. 19 N., R. 28 E., M. D. M., is sighted, bearing N.89°56' W., and from this the east and west center line of Section 26, aforesaid, by sight on the west $\frac{1}{4}$ corner bears S.89°25' W. This course determines the bearings used in this survey.

June 11, 1912:

Upon diligent search, and by recorded ties, all quarter and section corners necessary in Sections 26 and 35, T. 19 N., R. 28 E., are located and flags set on each corner.

I proceed to clear the center line of each section between flags rendering them intervisible and running through on each center line locate the intersection and the center of the section, marking the point in each section by a concrete post 24" x 5" x 5", marked 16/13, set 20" in the ground for the center of each section.

Dist.
Chains.

S. W. QUARTER, SECTION 26.

- Beginning at the southwest corner of section 26, I run N.0°15' E. on a true line along the west boundary of Section 26 toward a flag visible on this line.
- 18.44 Intersect dyke on south bank Carson River. Set concrete post 24" x 5" x 5", marked W.M.C., 20" in the ground U.S.R.S.
- for witness to meander corner.
- 23.36 Center of Carson River, ^{point for} meander corner.
- 39.90 West $\frac{1}{4}$ corner Section 26. Thence along the east and west center line Section 26 ^{toward the $\frac{1}{4}$ cor.} on which a flag is visible on a true line N.89°25' E.
- 40.52 Center Section 26, hereinbefore described.
(Retracing S.89°25' W., set redwood stake 3" x 3" x 24", marked 16/12, 20.26 chains, for 1/16 corner.)
^{beginning at the $\frac{1}{16}$ cor.} Thence along north and south center line of Section 26 on a true line toward the south $\frac{1}{4}$ corner, on which a flag is visible, S.0°14' W.,
- 39.95 S $\frac{1}{4}$ corner Section 26. Thence along the south boundary of Section 26 on a true line toward a flag visible on the S.W. corner, S.89°29' W.
- 21.94 Meander corner, center line "S" canal, inaccessible.
- 25.07 Intersect left right of way line "S" canal and set a concrete post 24" x 5" x 5", marked W.M.C., 20" in the ground, for witness to meander corner U.S.R.S.
- 40.54 S.W. corner Section 26, place of beginning.
(Retracing on true line, N.89°29' E., 20.27 chains, set redwood stake 3" x 3" x 24", marked 16/2, for 1/16 corner Section 35.)