

Dist.
Chains

-2-

BOUNDARY OF NORTHWEST QUARTER.

- Beginning at the N.W. corner, Section 30, I run along the north boundary on a true line N. $89^{\circ}59'$ E. Intersect N.W. or left right of way line of "S" Canal, 1.14 chains, from and parallel to the center line of said canal. Set concrete post 5" x 5" x 24", marked W.M.C., 20" in ground for witness to meander corner. U.S.R.S.
- 37.56 Center line "S" Canal, ^{point for} Meander corner.
38.92 Intersect right right of way line, set concrete post 5" x 5" x 24", marked W.M.C., 20" in ground. U.S.R.S.
- 40.17 North $\frac{1}{4}$ corner Section 30. Thence along the north and south center line of Section 30 on a true line S. $0^{\circ}21'$ E. Center of Section 30, hereinbefore described. Thence along the east and west center line of Section 30 on a true line S. $89^{\circ}54'$ W.
- 40.31 Intersect southeast or right right of way line of "S" Canal, 1.14 chains from and parallel to the center line of said canal. Set concrete post 5" x 5" x 24", marked W 1/4, 20" in ground. U.S.R.S.
- 38.70 Intersect southeast or right right of way line of "S" Canal, 1.14 chains from and parallel to the center line of said canal. Set concrete post 5" x 5" x 24", marked W 1/4, 20" in ground. U.S.R.S.
- 40.29 West $\frac{1}{4}$ corner Section 30, center line "S" Canal. Thence along west boundary Section 30, on a true line N. $0^{\circ}14'$ W. Intersect left right of way line "S" Canal, I set a concrete post 5" x 5" x 24", marked W 1/4, 20" in ground. Northwest corner, Section 30, and U.S.R.S. beginning point /

TRAVERSE "S" CANAL.

- It is impracticable to traverse and mark points along the center line of "S" Canal in the N.W. quarter of Section 30 afore mentioned. Therefore a line is run along to N.W. or left right of way line, 1.14 chains from and parallel to the center line of said "S" Canal, beginning at the witness corner to $1/4$ corner on the west boundary of this quarter section hereinbefore described, I run on a true line along the right of way boundary N. $44^{\circ}01'$ E. Set fir post 4" x 4" x 36", marked W.A.P., 24" in ground U.S.R.S.
- 47.78 for witness to angle points. Angle point bears S. $51^{\circ}30'$ E., 1.14 chains distant. Thence N. $33^{\circ}01'$ E.
- 5.23 Intersect concrete post on North boundary of Section 30, hereinbefore described.

The center line of the ^wcanal where used for the boundary between Lot 5 and Lot 6 is therefore:

- Beginning at the west $\frac{1}{4}$ corner of Section 30, and whence ^{witness} corners hereinbefore described bear N. $0^{\circ}14'$ W., 1.63 chains distant and N. $89^{\circ}54'$ E., 1.59 chains distant. Thence N. $44^{\circ}01'$ E.
- 49.06 Angle point whence witness stake hereinbefore described bears N. $51^{\circ}30'$ W., 1.14 chains distant. Thence N. $33^{\circ}01'$ E.
- 6.08 Meander corner of north boundary, Section 30, whence witness corners, hereinbefore described bear N. $89^{\circ}59'$ E. and S. $89^{\circ}59'$ W., 1.36 chains distant.

LOT 6.

- Beginning at the N.W. corner Section 30, run N. $89^{\circ}59'$ E. along north boundary.
- 36.20 Witness meander corner, hereinbefore described.
- 37.56 ^{Point for} Meander corner, center "S" Canal. Thence S. $33^{\circ}01'$ W. along center line "S" Canal.