

Beatty Townsite Nevada.

Survey of Boundary.

Chs. I begin at the quarter section corner between secs. 7 & 8, Tp. 12 S., Rg. 47 E., M.D.M. and run thence-
 South- along East boundary
 Over rolling country

20.00 To cor. No. 1 of Beatty Townsite Boundary.
 1320' Set a rhyolite stone 24 X 12 X 10 ins. 16 ins. in the ground marked B C L 1 on top (for Beatty City Limits); with mound of stone 3 ft. base, 2½ ft. high East of cor.

Thence from Cor. No. 1-
 West along South Boundary
 Over rolling country.

4.00 Center of bed of Amargosa river (nearly dry) course South.
 364'

8.03 Most easterly track of Bullfrog and Goldfield Ry. bears
 530' N. and S.

14.20 Main line Las Vegas and Tonapah Ry. bears N.10° W. and
 937' S.10°E.

60.00 To cor. No. 2- Set a rhyolite stone 24 X 18 X 10 ins.
 3960. 18 ins. in the ground marked B C L 2 on top, with mound of stone 3½ ft. base, 2 ft. high West of cor.

Thence from Cor. No. 2-
 North - along West boundary
 Over rolling country.

35.62 Center Las Vegas and Tonapah Ry., bears N.E. and S.W.
 2350.9'

40.00 To cor. No. 3- Set a rhyolite stone 20 X 12 X 6 ins.
 2640' 15 ins. in the ground marked B C L on S.E. and 3 on N.W. face, with mound of stone 3 ft. base, 2 ft. high N.W. of cor.

Thence from Cor. No. 3-
 East along north boundary.
 Over rolling and gently hilly country.