


## TOWNSHIP 42 NORTH, RANGE 62 EAST, OF THE MOUNT DIABLO MERIDIAN, NEVADA

## DEPENDENT RESURVEY


- Ⓕ Point for a witness point at the intersection of the line bet. secs. 7 and 18, with line 1-2, Mineral Survey No. 4864, Jungle No. 1 lode, from which the point for the E 1/16 sec. cor. of secs. 7 and 18, bears N. 89°54'40" E., 3.003 chs. dist., and Cor. No. 1, Mineral Survey No. 4864, Jungle No. 1 lode, bears N. 71°54'50" E., 3.233 chs. dist.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a rebar, 5/8 in. diam., 4 ft. long, driven vertically 3 1/2 ft. into loose mine tailings, and in a supporting mound of stone, 3 ft. base to top, with brass cap mkd.



- Ⓖ Point for a witness point at the intersection of the line bet. secs. 7 and 18, with line 2-3, Mineral Survey No. 4864, Jungle No. 1 lode, from which the 1/4 sec. cor. of secs. 7 and 18, bears S. 89°54'40" W., 10.854 chs. dist., and Cor. No. 2, Mineral Survey No. 4864, Jungle No. 1 lode, bears S. 18°05'10" E., 1.903 chs. dist.

Set a copper coated steel rod, 24 ins. long, 1/2 in. diam., 20 ins. in the ground, with brass cap, 1 1/4 ins. diam., mkd.



From which

A chiseled X followed by the letters B0, bears N. 87°35' W., 51.7 lks. dist., mkd. on the top surface of an igneous boulder, 5x2x1/2 ft. high.


A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 29°07' W., 102.9 lks. dist., with brass cap mkd. RM WP S7 67.9 FT TO COR 2017 and an arrow pointing to the point.

Corner falls on N. bank of creek, 5 lks. wide, 6 ins. deep, drains E.

- Ⓕ The 1/4 sec. cor. of secs. 7 and 18, determined by person(s) unknown, monumented with a rebar, of which no record was found, 5/8 in. diam., 18 ins. long, firmly set, flush with the top of a scattered mound of stone, 4 ft. diam., 1/2 ft. high. This position correlates well with other existing corners and calls of record, and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to solid rock, over a plastic-encased magnet, with brass cap mkd.




Deposit rebar inside stainless steel post and rebuild mound of stone, 4 ft. base, to top.

- Ⓐ The cor. of secs. 7 and 18 on the W. bdy. of the Tp., monumented with a basalt stone, 21x9x6 ins., firmly set, projecting 9 ins. above the ground, mkd. with 4 notches on S. edge, and 2 notches on N. edge, with an embedded mound of stone, 3 ft. diam., 1 ft. high, E. of corner and a steel fence post also set alongside. (Record: 16x9x6 ins.)

CORNER NOT REMONUMENTED

- Ⓙ Point for Cor. No. 1, Mineral Survey No. 4864, Jungle No. 1 lode, reestablished at record dist. from Cor. No. 4, Mineral Survey No. 4864, Jungle No. 1 lode, and on extension of line 4-1, Mineral Survey No. 4864, Jungle No. 2 lode, there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a rebar, 5/8 in. diam., 4 ft. long, driven vertically 3 1/2 ft. into loose mine tailings, and in a supporting stone base, set around the post and below the surface of ground, with brass cap mkd.




From which

A chiseled X followed by the letters B0, bears N. 58°12' E., 11 lks. dist., mkd. on the top surface of an igneous boulder, 7x4x2 ft. high, 1 ft. from E. edge.

Corner is located on steep N. tailings slope, 1 ch. southerly from base of slope overriding tributary of Dry Creek.

- Ⓚ Point for Cor. No. 2, Mineral Survey No. 4864, Jungle No. 1 lode, reestablished by the method of parallel side and end lines, there is no remaining evidence of the original corner.


Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a rebar, 5/8 in. diam., 4 ft. long, driven vertically 3 1/2 ft. into loose mine tailings, and in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.



- Ⓛ Cor. No. 3, Mineral Survey No. 4864, Jungle No. 1 lode, monumented with an iron post, 2 ins. diam., 4 1/2 ft. long, firmly set, projecting 12 ins. above a mound of stone, 4 ft. diam., 1 ft. high, with an unmarked copper plate, 2x3 ins., welded to top.

At the corner point


Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.



Deposit the iron post in mound of stone.

- Ⓜ Point for Cor. No. 4, Mineral Survey No. 4864, Jungle No. 1 lode, on line 4-1, Mineral Survey No. 4864, Jungle No. 2 lode, reestablished by the method of parallel side and end lines. The 1959 iron post, 2 ins. diam., 4 1/2 ft. long, with an unmarked copper plate, 2x3 ins., welded to top, lying loose on bank of road cut, alongside and NE. of cor. point, the original set position indeterminate.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.




Deposit the 1959 iron post in mound of stone.

From this point, Cor. No. 4, Mineral Survey No. 4864, Jungle No. 2 lode, bears N. 18°05'10" W., 2.068 chs. dist.

- Ⓝ Point for Cor. No. 1, Mineral Survey No. 4864, Jungle No. 2 lode, on line 4-1, Mineral Survey No. 4864, Jungle No. 1 lode, reestablished by the method of parallel side and end lines, there is no remaining evidence of the original corner.


Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.



From this point, Cor. No. 1, Mineral Survey No. 4864, Jungle No. 1 lode, bears S. 18°05'10" E., 2.068 chs. dist.

- Ⓞ Point for Cor. No. 2, Mineral Survey No. 4864, Jungle No. 2 lode, reestablished at record angle and record dist. from line 3-4, Mineral Survey No. 4864, Jungle No. 2 lode, there is no remaining evidence of the original corner.


Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.



- Ⓟ Cor. No. 3, Mineral Survey No. 4864, Jungle No. 2 lode, monumented with an iron post, 2 ins. diam., 4 1/2 ft. long, firmly set, projecting 22 ins. above the ground, with an unmarked copper plate, 2x3 ins., welded to top.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, over the upright lower portion of iron post left in place with upper 12 ins. cut off, and in a mound of stone, 3 ft. base, 1/2 ft. high, with brass cap mkd.




Bury upper portion of iron post with copper plate alongside stainless steel post.

- Ⓠ Cor. No. 4, Mineral Survey No. 4864, Jungle No. 2 lode, monumented with an iron post, 2 ins. diam., 4 1/2 ft. long, firmly set, projecting 20 ins. above the ground, with an unmarked copper plate, 2x3 ins., welded to top.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, over the upright lower portion of iron post left in place with upper 12 ins. cut off, and in a mound of stone, 3 ft. base, 1/2 ft. high, with brass cap mkd.



Bury upper portion of iron post with copper plate alongside stainless steel post.

## General Description

The land encompassed in this survey is high non forested rolling mountainous terrain of the Snake Mountains of far northeast Nevada. The project site is at an approximate elevation of 7000 ft. above sea level. Vegetation consists of sagebrush, bunchgrass and other low brush with aspen, willow, and wild rose in the drainages. The soil consists of loam deposits with the slopes of a tributary of Dry Creek, which drains easterly through the project, formed of mine tailings. The project area is located approximately 15 miles westerly of Nevada State Highway 93, and 30 miles north of the town of Wells, Nevada.

UNITED STATES DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

Reno, Nevada May 2, 2018

The survey represented by this plat, having been correctly executed in accordance with the requirements of law and the regulations of this Bureau, is hereby accepted.

For the Director

*Marshall O. Hammering*

Chief Cadastral Surveyor for Nevada